MINI SPORE AMPOULES For monitoring Steam Sterilisation processes.

Excelsior Code: OS1-50-06E

Product Description

Mini Spore Ampoules are Self-Contained Biological Indicators for monitoring Steam processes . Each kit consists of:

- Mini Spore Ampoules which contain modified Tryptic Soy Broth (TSB) with a pH indicator and Geobacillus stearothermophilus (Cell Line 7953). The modified TSB will transition will transition from the initial purple colour to yellow and or demonstrate turbidity in the presence of bacterial growth.
- Negative Control Ampoules which contain modified TSB with a pH indicator and a single glass bead to allow for clear segregation from the Spore Ampoules.

Indications for Use

The Mini Spore Ampoules may be utilized to monitor Steam sterilisation processes at 121°C to 137°C. The Spore Ampoules are ideal for monitoring liquid steam sterilisation cycles but may also be utilised in monitoring dry loads. Mini Spore Ampoules are labelled for industrial use only.

Instructions for Use

Exposure: Mini Spore Ampoules may be placed inside representative materials (containers of liquid) or within the chamber directly. Package or wrap product as usual, if applicable. Locate product or mini Spore Ampoules in most difficult location to sterilise, as outlined in your specific sterilisation validation protocol or according to standard operating procedure. Run the cycle.



Handle Mini Spore Ampoules with care as contents are extremely hot. Once Spore Ampoules are cooled and able to be handled, remove from steriliser immediately. Leaving the Mini Spore Ampoules in the steriliser post-exposure may have a negative impact on the product's performance. As such, Mini Spore Ampoules left in the chamber for extended periods of time (24 hours) post-exposure should be discarded.

After sterilisation or exposure, remove Mini Spore Ampoules or product from steriliser. Allow product or Spore Ampoules to cool to the touch. No activation is required.

Incubation: Place the processed Mini Spore Ampoules, one Negative Control Ampoule and one Positive Control (unprocessed Mini Spore Ampoule) in a vertical position in an incubator at 55°C to 65°C for a minimum of 48 hours.

Monitoring: Examine the Mini Spore Ampoules daily during incubation. Record observations. All positive Mini Spore Ampoules should be disposed of immediately. Do not continue to incubate a positive Ampoule. Continued growth may result in metabolism of amino acids in the absence of sugars, causing the pH to rise and result in colour reversion that is visibly darker than a sterile unit. These should be considered as positive for growth (turbidity will be present).

For unexpected positives, it is recommended that a Gram stain be performed. Gram positive rods are Indicative for the indicator organism.

Interpretation: Negative Control: The Negative Control Ampoule should not exhibit a colour change to yellow and/or demonstrate turbidity. Utilise the Negative Control as a colour comparison for the exposed Mini Spore Ampoules, where applicable.

Positive Control Mini Spore Ampoule: The Positive Control Ampoule should exhibit a colour change to yellow and/or demonstrate turbidity. Utilise the Positive Control as a colour comparison for the exposed ampoules, where applicable. If the positive control does not demonstrate a yellow colour and/or turbidity, the results for the test ampoules should not be considered valid. Verify incubation conditions were met.

Test Mini Spore Ampoules: A passing sterilisation cycle is indicated by a test Spore Ampoule which retains its original purple colour and is free from turbidity. A failed sterilisation cycle is indicated by turbidity and/or

Physical Properties

Process	Steam
Dimensions	40 mm x 6.5mm
Packaging	Mini Spore Ampoules: 50 per box Negative Control Ampoules: 5 per Box
Volume	0.7mL

Monitoring Frequency

For greatest control of sterilised goods, it is recommended that one or more Mini Spore Ampoules be included with every load.

Performance Characteristics

Population	≥ 1.0 x 10 ⁶ ampoule		
Purity	No evidence of contamination present in sufficient numbers to adversely affect the finished product.		
Steam Resistance	D value at 121°C ± 0.5°C ≥ 1.5 minutes The Steam D value range is based on the requirements outlined in the USP, ISO 11138-3 and guidance issued by the Food & Drug Administration (FDA). Survival – Kill Times Calculated based on the formulations outlined in the USP, ISO 11138-1 and guidance issued by the FDA. z value ≥ 6°C Determined based on three temperatures in the range of 118°C to 138°C. Excelsior Scientific typically utilises D values determined at 118°C, 121°C and 130°C for z value calculation.		
Population: 50% to 300% of certified population D value: ± 20% of the certified D value Survival Time: All Spore Ampoules result in growth at the certified survival time Kill Time: All Spore Ampoules result in no growth at the certified kill time			

Compliance

ISO 11138-1 Sterilization of health care products – Biological Indicators- Part 1:General Requirements

ISO 11138-3 sterilisation of healthcare products—Biological Indicators –Part 3: Biological Indicators for moist heat sterilization processes.

USP <55> Biological Indicators— Resistance Performance Tests

Excelsior Scientific has a validated method for Total Viable Spore Count. Please inquire for the Technical Bulletin entitled "Population Verification for Spore Ampoules" to ensure consistent methodologies are being utilised when performing verification testing.

USP Biological/Official Monographs

USP Biological Indicator for Steam Sterilization, Self-Contained

Storage and Shelf Life

+2°C +8°C	Refrigerate at 2°C to 8°C	类	Keep away from Sunlight	
	Do not freeze	淡	Protect from heat, radioactive sources & sterilising agents	
Shelf Life	24 months from the date of manufacture.			
\triangle	Do not use damaged Mini Spore Ampoules or Mini Spore Ampoules which demonstrate turbidity or have transitioned to a yellow colour. Do not use after expiration date. The Mini Spore Ampoules contain live cultures and should be handled with care.			

Disposal

Autoclave for not less than 30 minutes at 121°C or per validated disposal cycle prior to discard.

